



## BEARING DRIVESHAFT, INC.



6000 Bearing 2D drawings and 3D CAD models

NTN Timken NSK NACHI Koyo SKF 6000  
6001 6002 6003 6004 6005 Open Zz 2RS Ball  
Bearing for Motorcycle/Engine/Electric  
Motor/Pump/Power Generator

Bearing No. 6000

Size	10x26x8 mm
Bore Diameter	10 mm
Outer Diameter	26 mm
Width	8 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
r min.	0.3 mm
da min.	12 mm
Da max.	24 mm
ra max.	0.3 mm
Weight	0.019 Kg
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,97 kN
(Grease) Lubrication Speed	30000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	10 mm
Outside Diameter	26 mm
Width	8 mm
Fillet Radius/Chamfer	0.3 mm



## BEARING DRIVESHAFT, INC.

Dynamic Load Rating	4,550 N
Static Load Rating	1,970 N
Limiting Speed - Grease	30,000 rpm
Limiting Speed - Oil	36,000 rpm
Factor $f_0$	12.4
Radial Clearance	0.002 to 0.013 mm
$d_a$ (min)	12 mm
$D_a$ (max)	24 mm
$r_a$ (max)	0.3 mm